


CATV COAXIAL CABLES | PVC



COAXIAL CABLES

TYPE	SHIELD	PART NO.	AWG	NOMINAL OD (INCH)		NEC TYPE	SHIP WT / 1M'
				CORE	CABLE		
RG 59	Foil + 45% AL	4-4590	20 BCCS	.146	.240	CATV CM	21
	Foil + 53% AL	4-4599	22 BCCS	.140	.240	CATV	23
	Foil + 65% AL	4-4591	20 BCCS	.146	.242	CATV	23
RG 6	Foil + 40% AL	4-4069	18 BCCS	.180	.270	CATV CM	26
	Foil + 60% AL	4-4061	18 BCCS	.180	.270	CATV CM	30
	Foil + 60% AL	4-4061R	18 BCCS	.180	.270	CATVR CMR	30
	Foil + 60% AL	4-4061M	18 BCCS	.180	.270 x.401	CATV CM	48
	Foil + 60% AL	4-4061D	18 BCCS x 2	.180	.270 x .570	CATV	61
	Foil + 60% AL	4-4061DM	18 BCCS x 2	.180	.270 x .703	CATV	75
	Foil + 60% AL Foil + 40% AL	4-4061QS	18 BCCS	.180	.298	CATV CM	35
	Foil + 60% AL	4-4068	18 BC	.180	.270	CATV CM	29
	Foil + 60% AL Foil + 40% AL	4-4068QS	18 BC	.180	.300	CATV CM	34
	Foil + 90% AL	4-4060	18 BCCS	.180	.270	CATV CM	29
RG11	Foil + 60% AL Foil + 40% AL	4-4011QS	14 BC	.280	.430	CM	65
	Foil + 65% AL	4-4111	14 BCCS	.280	.405	CM	60
	Foil + 60% AL Foil + 40% AL	4-4111QS	14 BCCS	.280	.430	CM	65

The information contained on this specification is intended to be used as a guide and every effort has been made to ensure its accuracy at time of publication. This specification is subject to change anytime without notice. Please refer to www.adcable.com for the most up to date information. Rev 0419

PRODUCT DESCRIPTION

Foamed dielectric core over solid copper or copper covered steel center conductor, bonded aluminum foil, aluminum braid shield, overall black PVC jacket*.

APPLICATIONS

- Audio/Video
- CATV

SPECIFICATIONS

Nominal Impedance 75 Ohm
Nominal Velocity of Propagation 82
Nominal Capacitance 16.2
NEC Articles: CATV, CATVR, CMR, CM
Temp. Rating -30°C to +75°C
 Sunlight Resistant
Attenuation see chart on page 47
 (RG6 & RG11 are 3GHz swept tested)

AVAILABLE PUT-UPS

1,000' Reels and Boxes
 500' Reels and Boxes
 Other lengths available. Please consult your factory representative for availability.

CABLE IDENTIFICATION

RG X XX AWG (UL) TYPE CATV
 c(UL)us TYPE CM E179333

- * Other colors available upon request. Please consult factory for minimums and lead times.
- * Riser rated/FT4 available upon request



(800) 343 2579 • www.adcable.com